KRAMER ELECTRONICS, Ltd.
www.kramerelectronics.com

C-FM6/FM4

6−pin to 4−pin FireWire® Cable

Kramer's FM6/FM4 cables are high−performance cables with 6−pin FireWire® connectors at one end, and a 4−pin connector at the other. They are used primarily for data transfer (IEEE 1394) at speeds up to 400Mbps between multimedia devices such as digital cameras, VCRs, CD drives, hard disks, scanners, graphic cards and editing systems.

FEATURES

- Quality Construction - Constructed using two separately double−shielded data cables, in an overall double−shielded outer jacket.
- High-Quality Connectors - Has a molded 4−pin connector on one end, and a molded 6−pin connector on the other. The 4−pin connector is popular on cameras and other small devices due to its compact size, but PC's and other larger devices often use the 6−pin.
- Varied Selection of Lengths - Available in versions of 0.9 to 7.6m (3, 6, 10, 15 and 25ft).

Model	Description	Length	Meter
Male - Male			
C-FM6/FM4-3	6-Pin (M) to 4-Pin (M) FireWire Cable	3'	0.9M
C-FM6/FM4-6	6-Pin (M) to 4-Pin (M) FireWire Cable	6'	1.8M
C-FM6/FM4-10	6-Pin (M) to 4-Pin (M) FireWire Cable	10'	3.0M
C-FM6/FM4-15	6-Pin (M) to 4-Pin (M) FireWire Cable	15'	4.6M
C-FM6/FM4-25	6-Pin (M) to 4-Pin (M) FireWire Cable	25'	7.6M